

### RIGID FRAME FUEL & LUBE TRUCKS

4,000 - 25,000 gallons 15,141 - 94,635 liters



OPTIMIZE YOUR SERVICE INTERVALS

#### **GROUND FORCE WORLDWIDE**

# RIGID FRAME FUEL & LUBE TRUCKS

## **ENGINEERED FOR PERFORMANCE**

Ground Force Rigid Frame Fuel & Lube Trucks are ENGINEERED FOR PERFORMANCE and built to last. Our fuel and lube trucks are adaptable to fit any rigid frame chassis on the market today and are developed specifically for moving large volumes of product in high production mining applications.

We offer many configurations and custom features as well as heated and enclosed fuel and lube trucks for extreme and cold weather applications. Ground Force Rigid Frame Fuel and Lube Trucks are PROVEN to INCREASE EFFICIENCY and REDUCE MAINTENANCE COST for your operation.









Capacities may vary depending on chassis size, weight distribution and custom

#### **RIGID FRAME FUEL & LUBE BODIES:**

and custom requirements.				
		CLASS	CAPACITY	MODEL
		OPEN	N DECK FUEL & LUBE TRUCKS / ENCLOSED FUEL & LUBE TRUCKS (Arctic Applications)	
		40 T (36 mt)	Diesel: 4,000 gal. (15,141 L) Lubricants: 2,250 gal. (8,517 L) Grease: 1100 lb. (499 kg)	40FL/EFL
		60 T (55 mt)	Diesel: 5,500 gal. (20,819 L) Lubricants: 2,250 gal. (8,517 L) Grease: 1100 lb. (499 kg)	60FL/EFL
		70 T (63.5 mt)	Diesel: 5,500 gal. (20,819 L) Lubricants: 2,250 gal. (8,517 L) Grease: 1100 lb. (499 kg)	70FL/EFL
		100 T (90 mt)	Diesel: 10,000 gal. (37,854 L) Lubricants: 4,500 gal. (17,034 L) Grease: 3200 lb. (1,588 kg)	100FL/EFL
	1	50 T (134 mt)	Diesel: 18,000 gal. (68,137 L) Lubricants: 5,500 gal. (20,819 L) Grease: 3500 lb. (1,588 kg)	150FL/EFL
,	2	200 T (177 mt)	Diesel: 22,000 gal. (83,279 L) Lubricants: 7,500 gal. (28,390 L) Grease: 3500 lb. (1,588 kg)	200FL/EFL
	2	50 T (227 mt)	Diesel: 25,000 gal. (94,635 L) Lubricants: 9,400 gal. (35,582 L) Grease: 3500 lb. (1,588 kg)	250FL/EFL





#### **SPECIAL FEATURES**

- Fuel delivery 120-300 GPM (454-1,135 LPM)
- Full product filtration
- Fully baffled product tanks
- Product metering systems
- Product tank level gauges

#### **OPERATOR EASE & SAFETY**

- Ground-level/remote-fill for all products
- Micro-controller is bluetooth capable for easy troubleshooting and configuration changes by app-based technology where wifi is present.
- New and used filter storage
- Enclosed ground level rear and/or side reel compartments
- · Mine-site lighting packages
- Anti-Slip walkways and handrails

#### **PRODUCT AVAILABILITY & OPTIONS**

- Diesel capacity from 4,000 to 25,000 gal. (15,141 to 94,635 L)
- New oil and coolant capacity from 2,000 to 8,200 gal. (7,571 31,401 L)
- Grease bins from 800 to 3,500 lb. (363 1,306 kg)
- · Heated product tanks available
- Spring, Hydraulic, and Electric reel available
- Enclosed & heated body for arctic applications
- Used oil and coolant tanks
- Air compressor with reservoir tank
- Optional high pressure wash system
- Systems powered by chassis hydraulics or diesel-driven Auxiliary Power Unit (APU)
- Kidney-loop filtration systems
- Roll-over protection system
- \*Ground Force Field Service Available

### OPTIONAL FLUID LEVEL MONITORING SYSTEM

In-cab fluid level monitoring for all product tanks

 Digitally controlled monitor with backlit LCD for low-light operations

Touch screen functionality and expandable system components available for alternate locations













#### THE GROUND FORCE DIFFERENCE

Innovative & Diverse Products
Loyalty & Devotion to our Customers
Global Service & Support



6001 E. Seltice Way
Post Falls, ID 83854 U.S.A.
+1.208.664.9291 | Fax 208.664.9475
solutions@gfworldwide.com
gfworldwide.com