

AGILE BY DESIGN, ENGINEERED TO EXCEL





Ground Force Articulated Fuel and Lube Bodies are custom-engineered with specifications that suit your individual operation and are manufactured to endure extreme conditions and rugged applications.

Our engineering team ensures your Ground Force Fuel and Lube Truck is optimally sized, balanced, and built for longevity. Designed with operator safety and efficiency in mind, we strategically engineer smart locations for service points and ground-level operator stations for filling and dispensing.

Ground Force Worldwide is the world leader in articulated fuel and lube trucks, with 200+ trucks in mines across the world today.



FUEL & LUBE TRUCKS

25 - 45 tons / 23 - 41 metric ton

AVAILABLE ARTICULATED FUEL & LUBE TRUCK MODELS

Open deck and enclosed models for arctic applications.

CLASS	CAPACITY	MODEL
25 T (23 mt)	Diesel: 2,500 gal. (9,463 L) Lubricants: 930 gal. (3,520 L) Grease: 750 lb. (340 kg)	25FL 25EFL
30 T (28 mt)	Diesel: 3,500 gal. (13,248 L) Lubricants: 1,200 gal. (4,542 L) Grease: 750 lb. (340 kg)	30FL 30EFL
35 T (32 mt)	Diesel: 4,000 gal. (15,141 L) Lubricants: 1,500 gal. (5,678 L) Grease: 1,100 lb. (499 kg)	35FL 35EFL
40-45 T (39-41 mt)	Diesel: 5,000 gal. (18,927 L) Lubricants: 1,500 gal. (5,678 L) Grease: 1,100 lb. (499 kg)	40FL/40EFL 45FL/EFL

Capacities shown may vary depending on chassis size, weight distribution, options and custom requirements.





SPECIAL FEATURES

- Fuel delivery 120-300 GPM (454-1,135 LPM)
- Full product filtration
- Fully baffled product tanks
- Product metering systems
- Product tank level sight eyes

OPERATOR EASE & SAFETY

- Ground-level/remote-fill for all products
- New and used filter storage
- Enclosed ground level rear and/or side reel compartments
- Mine-site lighting packages
- Anti-Slip walkways and handrails
- Micro-controller is bluetooth capable for easy troubleshooting and configuration changes by app-based technology where wifi is present.

PRODUCT AVAILABILITY & OPTIONS

- Diesel capacity 4,000-25,000 gal. (15,141-94,635 L)
- New oil and coolant capacity 2,000-8,200 gal. (7,571-31,040 L)
- Grease bin system from 800-3,500 lb. (363-1,306 kg)
- Spring, hydraulic, and electric reel options
- Enclosed & heated body for arctic applications
- Used oil and coolant tanks
- Air compressor with reservoir tank
- Systems powered by chassis hydraulics or diesel-driven Auxiliary Power Unit (APU)
- Kidney-loop filtration systems
- Roll-over protection system
- Optional heated product tanks
- Optional high pressure wash system
- Optional Ground Force chassis frame stretch

Field Service & Training Guidance Available



OPTIONAL FLUID LEVEL MONITORING SYSTEM - FLM

- Fluid Level Monitoring for main diesel tank and all fluids
- Digital in-cab control monitor with backlit LCD for low-light operations
- Touch screen functionality and expandable system components for future upgrades





- O 6001 E. Seltice Way Post Falls, Idaho 83854 U.S.A.
- Solutions@gfworldwide.com
- +1 (208) 664-9291
- gfworldwide.com