

Fuel & Lube **SKIDS**

5,000 - 100,000 gallons / 18,927 - 378,541 liters



PEAK EFFICIENCY,
OPTIMUM YIELD

GROUND FORCE
WORLDWIDE
WORLD'S FINEST MINE SUPPORT EQUIPMENT

Fuel & Lube **SKIDS**



Ground Force Fuel and Lube Skids deliver superior performance while offering a variety of options. These units offer cost savings while still allowing you a mobile solution. Easily towed by a track-type tractor makes transport efficient as your operation grows.

Engineered to offer diverse arrangements, including office spaces, workspace and restrooms, Ground Force Fuel and Lube Skids provide the best return on investment in a mobile asset.



AVAILABLE FUEL AND LUBE SKID MODELS

CLASS	CAPACITY
Fuel Only	Fuel: 5,000 – 100,000 gal. (18,927 – 378,541 L)
Lube Only	Lubricant: 11,400 – 40,000 gal. (43,153 – 151,416 L) Grease: 1,100 – 3,500 lb. (498 – 1,587 kg)
Fuel & Lube	Fuel: 10,000 – 100,000 gal. (37,854 – 378,541 L) Lubricant: 2,000 – 10,000 gal. (7,570 – 37,854 L) Grease: 1,100 – 3,500 lb. (498 – 1,587 kg)
Diesel Exhaust Fluid (DEF)	DEF: 5,000 – 10,000 gal. (18,927 – 37,854 L)

Capacities shown may vary depending on chassis size, weight distribution, options and custom requirements.

Modules built on skids, for easy transport by lowboy or towing by track-type tractor.





SPECIAL FEATURES

- Fuel delivery 120 - 300 GPM (454-1,135 LPM)
- Full product filtration
- Baffled product tanks
- Product metering systems
- Product tank level sight eyes

OPERATOR EASE & SAFETY

- Built on skids for easy transport by lowboy or towing with track-type tractor
- Ground-level/remote-fill for all products
- New and used filter storage
- Enclosed ground level, rear and/or side reel compartments
- Mine-site lighting packages
- Anti-Slip walkways and handrails

LUBE/EQUIPMENT “DOG-HOUSE”

- Includes machinery and product tank enclosure
- Mounted directly to heavy-duty skid frames
- Single or multiple reel rack assembly
- Built-in spill containment

PRODUCT AVAILABILITY & OPTIONS

- Diesel capacity 5,000-100,000 gal. (18,927-378,541 L)
- New oil and coolant capacity 2,000-10,000 gal. (7,570-37,854 L)
- Grease bin systems from 1,100-3,500 lb. (498-1,587 kg)
- Spring, Hydraulic, and Electric reel available
- Used oil and coolant tanks
- Air compressor with reservoir tank
- Systems powered by chassis hydraulics or diesel-driven Auxiliary Power Unit (APU)
- Kidney-loop filtration systems
- Single or multiple reel rack assembly
- Optional heated product tanks available
- Optional office space, workspace, and restrooms
- Optional insulated and heated and/or AC configurations

FUEL TANK SYSTEMS

- Double wall certified tanks
- Mounted directly to heavy-duty skid frames
- Vents on primary and secondary tanks
- Sight eyes
- Leak detection system
- High-efficiency filtration system
- Top-of-tank catwalk assembly

Field Service & Training Guidance Available



OPTIONAL - FLUID LEVEL MONITORING SYSTEM (FLM)



- Fluid Level Monitoring for main diesel tank and all fluids
- Digital in-cab control monitor with backlit LCD for low-light operations
- Touch screen functionality and expandable system components for future upgrades



For more information
contact us online at
gfworldwide.com.



6001 E. Seltice Way
Post Falls, Idaho 83854 U.S.A.



Solutions@gfworldwide.com



+1 (208) 664-9291



gfworldwide.com