

Rigid Frame

FUEL & LUBE TRUCKS

40 - 240 tons / 36 - 227 metric ton

4,000 - 25,000 gallons / 15,141 - 94,635 liters



RELIABILITY, DURABILITY, AND
A TRUE LEGACY OF EXCELLENCE

GROUND FORCE
WORLDWIDE
WORLD'S FINEST MINE SUPPORT EQUIPMENT



Adaptable to any rigid frame chassis, our Fuel and Lube Bodies are engineered for efficiently handling large product volumes in high-production mining applications. Built to last, these trucks ensure reliability in demanding environments.

Diverse configurations and custom features include heated and enclosed options for extreme conditions.

Ground Force Rigid Frame Fuel & Lube Trucks have a proven track record of boosting efficiency and cutting maintenance costs in demanding operations. Choose reliability for your success.



Enclosed and heated bodies for extreme conditions.

Rigid Frame **FUEL & LUBE TRUCKS**

40 - 240 tons / 36 - 227 metric ton

AVAILABLE RIGID FRAME FUEL & LUBE MODELS

Open deck and enclosed models for arctic applications.

CLASS	CAPACITY	MODEL
40 T (36 mt)	Diesel: 4,000 gal (15,141 L) Lubricants: 2,250 gal (8,517 L) Grease: 1,100 lb (411 kg)	40FL
60 T (55 mt)	Diesel: 6,200 gal (23,469 L) Lubricants: 2,250 gal (8,517 L) Grease: 1,100 lb (411 kg)	60FL
70 T (63.5 mt)	Diesel: 6,200 gal (23,469 L) Lubricants: 2,250 gal (8,517 L) Grease: 1,100 lb (411 kg)	70FL
100 T (90 mt)	Diesel: 10,000 gal (37,854 L) Lubricants: 4,500 gal (17,034 L) Grease: 3,200 lb (1,194 kg)	100FL
150 T (134 mt)	Diesel: 18,000 gal (68,137 L) Lubricants: 5,500 gal (20,819 L) Grease: 3,500 lb (1,306 kg)	150FL
200 T (177 mt)	Diesel: 22,000 gal (83,279 L) Lubricants: 7,500 gal (28,390 L) Grease: 3,500 lb (1,306 kg)	200FL
250 T (227 mt)	Diesel: 25,000 gal (94,635 L) Lubricants: 9,400 gal (35,582 L) Grease: 3500 lb (1,306 kg)	250FL

Capacities shown may vary depending on chassis size, weight distribution, options and custom requirements.





SPECIAL FEATURES

- Fuel delivery 120-300 GPM (454-1,135 LPM)
- Full product filtration
- Fully baffled product tanks
- Product metering systems
- Product tank level sight eyes

OPERATOR EASE & SAFETY

- Ground-level/remote-fill for all products
- New and used filter storage
- Enclosed ground level rear and/or side reel compartments
- Mine-site lighting packages
- Anti-Slip walkways and handrails
- Micro-controller is bluetooth capable for easy troubleshooting and configuration changes by app-based technology where wifi is present.

PRODUCT AVAILABILITY & OPTIONS

- Diesel capacity 4,000-25,000 gal. (15,141-94,635 L)
- New oil and coolant capacity 2,000-8,200 gal. (7,571-31,040 L)
- Grease bin systems from 800-3,500 lb. (363-1,306 kg)
- Spring, hydraulic, and electric reel options
- Enclosed & heated body for arctic applications
- Used oil and coolant tanks
- Air compressor with reservoir tank
- Systems powered by chassis hydraulics or diesel-driven Auxiliary Power Unit (APU)
- Kidney-loop filtration systems
- Roll-over protection system
- Optional high pressure wash system
- Optional heated product tanks

Field Service & Training Guidance Available




OPTIONAL FLUID LEVEL MONITORING SYSTEM - FLM

- Fluid Level Monitoring for main diesel tank and all fluids
- Digital in-cab control monitor with backlit LCD for low-light operations
- Touch screen functionality and expandable system components for future upgrades





For more information
contact us online at
gfworldwide.com.

 6001 E. Seltice Way
Post Falls, Idaho 83854 U.S.A.

 Solutions@gfworldwide.com

 +1 (208) 664-9291

 gfworldwide.com